

For more information click on product image	Chipset, CPU	Network	Memory Storage	Dimensions WxDxH / Weight Noise (idle) Power / Consumpt.(idle)	Warranty Certificate	External I/O Ports	Test Status TCP-Throughput (Red -> Green)				
							pfSense v2.3.4	OPNsense v17.7	IPFire v2.19	RouterOS v6.x	ClearOS v7.2
 <b>SBR234-FW</b>	Intel Braswell 14nm Dual Celeron N3050 2x 1.6-2.16 GHz	<b>3x</b> PCIe GBit Ethernet 2x Intel 82576 + 1x RTL8111H  Option <b>5x</b> PCIe GBit 4x Qualcomm AR8131 + 1x RTL8111H	RAM: 2GB DDR3 Option: 4GB, 8GB  Storage (2.5" HDD): 32GB MLC SATA3 SSD Option: 120GB SSD, 500GB classic HDD Option: Internal USB-Flash 16GB, 64GB	311x241x65mm 2.5 kg <b>noiseless</b> Ext. 12V 5A / <b>14w</b>	36 months CE, FCC, RoHS, WEEE	3-7x RJ45 2x PS/2 1x VGA 1x HDMI 2x USB3 2x USB2 1x COM	compatible 710 MBit	compatible 710 MBit	compatible 580 MBit	compatible 820 MBit	compatible 650 MBit
 <b>SBR234-1U-FW</b>	Option CPU Upgrade Quad Celeron N3150	<b>3x</b> PCIe GBit Ethernet 2x Intel 82576 + 1x RTL8111H  Option <b>5x</b> PCIe GBit 4x Intel 82580 + 1x RTL8111H Option <b>7x</b> PCIe GBit 6x Intel 82571EB + 1x RTL8111H	483x250x44mm 19" 1U Rack 5.6 kg ~ 27 db Int. 250w / 17w								
 <b>SBR701-FW</b>	Intel H110 LGA1151 Intel G4400 2x 3.3 GHz	<b>3x</b> PCIe GBit Ethernet 2x Intel 82576 + 1x RTL8111H  Option <b>5x</b> PCIe GBit 4x Intel 82580 + 1x RTL8111H Option <b>7x</b> PCIe GBit 6x Intel 82571EB + 1x RTL8111H Option <b>10Gbit</b> 2x intel 10Gbit <b>x550-t2</b> + 1x RTL8111H	RAM: 2GB DDR3 Option: 4GB, 8GB, 16GB  Storage (2.5" HDD): 32GB MLC SATA3 SSD Option: 120GB SSD, 500GB classic HDD Option: Internal USB-Flash 16GB, 64GB	311x241x65mm 2.6 kg, ~ 27 db Ext. 12V 5A / <b>19w</b>	36 months CE, FCC, RoHS, WEEE	3-7x RJ45 1x HDMI 1x PS/2 2x USB3 4x USB2	compatible 880 MBit  10Gbit <b>x550</b> compatible 6400 MBit	compatible 880 MBit	compatible 880 MBit	compatible 880 MBit	compatible 880 MBit
 <b>SBR701-1U-FW</b>	Option CPU Upgrade LGA1151 CPU Pentium, i3, i5, i7	483x250x44mm 19" 1U Rack 5.7 kg, ~ 30 db Int. 250w / 23w									
 <b>SBR4LAN2</b>  2x devices	2x Intel Celeron quad J1900 4x 2.0-2.42 GHz	2x 4x Intel 82580	RAM: 2GB DDR3 Option: 4GB, 8GB Storage: 16GB MSATA Option: 32GB, 64GB	483x250x44mm 19" 1U Rack 2.5 kg <b>fanless</b> Ext. 12V 5A / <b>9w</b>	36 months CE, FCC, RoHS, WEEE	4x RJ-45 1x VGA 1x USB3 1x USB2 1xCOM (RJ45)	compatible 780 MBit	compatible 780 MBit	compatible 650 MBit	compatible 820 MBit	compatible 650 MBit
 <b>SBR711-FW</b>	Intel H110 LGA1151 Intel G4400 2x 3.3 GHz	<b>3x</b> Intel PCIe GBit Ethernet 2x 82576 + 1x i219V  Option <b>5x</b> PCIe GBit 4x Intel 82580 + 1x i219V  Option <b>7x</b> PCIe GBit 6x Intel 82571EB + 1x i219V Option <b>10Gbit</b> 2x intel 10Gbit <b>x550-t2</b> + 1x i219V	RAM: 4GB DDR4 Option: 8GB, 16GB, 32GB  Storage (2.5" HDD): 32GB MLC SATA3 SSD Option: 120GB SSD, 500GB classic HDD Option: Internal USB-Flash 16GB, 64GB	311x241x65mm 2.5 kg, ~ 25 db Ext. 12V 5A / 19w							
 <b>SBR711-1U-FW</b>	Option CPU Upgrade LGA1151 CPU Pentium, i3, i5, i7	483x250x44mm 19" 1U Rack 5.7 kg, ~ 30 db Int. 250w / 23w	36 months CE, FCC, RoHS, WEEE	compatible 880 MBit  10Gbit <b>x550</b> compatible 6400 MBit	compatible 880 MBit	compatible 880 MBit	compatible 880 MBit Onboard NIC i219V not recognized	compatible 880 MBit			
 <b>SBR706-1U-FW</b>	Intel C222 quad <b>Xeon</b> E3-1220V3 LSI MegaRAID	<b>6x</b> Intel PCIe GBit Ethernet 4x 82580 + 2x i210AT Option <b>10Gbit</b> 2x intel 10Gbit <b>x550-t2</b> + 1x i210V Option: Management LAN (PMI, iKVM)	RAM: 4GB DDR3 ECC Storage: 120GB MLC SATA3 SSD Option: 500GB classic HDD Option: Internal USB-Flash 16GB, 64GB	483x250x44mm <b>19" 1U Rack</b> 6.5 kg, ~ 35 db Int. 250w / 35w	36 months CE, FCC, RoHS, WEEE	6x RJ45 1x PS/2 1x DVI 2x USB3 2x USB2	compatible 880 MBit 10Gbit <b>x550</b> compatible 7500 MBit	compatible 880 MBit	compatible 880 MBit	compatible 880 MBit Onboard NIC i210AT not recognized	compatible 880 MBit

## Sylbek Firewall - Desktop 311x241x65mm



© www.sylbek.eu You may use this graphic for any purpose, if you leave the copyright in place.

## Sylbek Firewall Hardware Platform

Prices do not include VAT and shipping cost

Product Name	1 pc	3 pcs	10 pcs
SBT110F	399 €	390 € / 2,3 %	ask
SBR234-FW	325 €	299 € / 8,7 %	ask
SBR234-1U-FW	436 €	412 € / 5,8 %	ask
SBR701-FW	439 €	412 € / 6,6 %	ask
SBR701-1U-FW	549 €	525 € / 4,6 %	ask
SBR4LAN2	799 €	729 € / 9,6 %	ask
SBR711-FW	449 €	415 € / 8,2 %	ask
SBR711-1U-FW	549 €	525 € / 4,6 %	ask
SBR706-1U-FW	999 €	935 € / 6,8 %	ask

## Sylbek Firewall Platform - 19" 1U 483x250x44mm



© www.sylbek.eu You may use this graphic for any purpose, if you leave the copyright in place.

### Common Properties

- Powerful Firewall Systems with minimal power consumption
- Selected Hardware with proven components to achieve wide compatibility/stability with Linux and BSD operating systems
- Modular design for easy replacing of parts like: common DDR3/DDR4 memory, SATA and and PCIe interfaces
- Industrial SLC storage for operating system, MLC storage for backups, FTP, WWW Server ...
- In-stock product, delivery in 1-2 days, delivery capacity for large quantity
- 3 years bring-in warranty with repair/replace within 1-3 days

### Gemeinsame Eigenschaften

- Leistungsfähige Firewall Systeme trotz minimalem Energieverbrauch
- Ausgesuchte Hardware, mit bewährten Komponenten wegen Kompatibilität/Stabilität mit vielen Linux und BSD Betriebssystemen
- Modularer Aufbau mit leicht austauschbaren Komponenten, wie Standard DDR3/DDR4 Speicher, SATA Schnittstelle, PCIe Netzwerkkarten
- Industrie SLC Speicher für Betriebssystem, MLC Speicher für Backup, FTP, WWW Server ...
- Lagerware, Lieferung in 1-2 Tagen, Lieferfähigkeit in grossen Stückzahlen
- 3 Jahre Bring-in Garantie, mit Reparatur/Austausch innerhalb von 1-3 Tagen